

Description

- Operation mode and max sensing range:
Thru-beam: 1-10 m
- Cable or plug connection
- Sensitivity adjustment via control input
- Power and output indicator
- 10 – 30 V dc supply voltage
- 3 wire, NPN or PNP transistor output
- Narrow optical beam
- TÜV approved as safety device (AOPD) for power operated doors and gates acc. EN12978



The 3000/CAT2 series consists of a self-contained transmitter SMT and a receiver SMR, which are to be used in thru beam mode. The complete series is available in a wide range of housings with either cable or plug connection.

The SMR is supplied with a 10-30 V dc supply voltage with a 3 wire, NPN or PNP transistor output in light operated.

The control input in the SMT may be used for either disabling or enabling the transmitting power temporarily for test purpose, multiplexing applications or as a gradual regulation of the transmitting power level.

Both the transmitter and receiver are protected against reverse polarity of power supply, control input and output signal. The output is also protected against short circuit and inductive loads.

Technical Data		
	SMT	SMR
	3010C/CAT2	3x10/CAT2
Supply voltage	10-30 V dc	
Voltage ripple	Max. 15 %	
Reverse polarity protected	Yes	
Short circuit protected	-	Yes
Current consumption	Max. 30 mA	Max. 8 mA
Maximum output load	-	100 mA
Maximum residual voltage	-	2,5 V
Maximum operation frequency	-	> 15 Hz
Response time t_{ON} / t_{OFF}	-	< 14 ms / < 34 ms
Power on indicator	Green LED	-
Output indicator	-	Yellow LED
Hysteresis	-	Approx. 25 %
Light source	Infrared (880 nm)	-
Opening angle	-	+/- 2°
Emission angle	+/- 2°	-
Housing material	Sensor housing	Nickel Plated Brass or Polycarbonate
	Front lens	Polycarbonate
Cable, PVC Ø 3,4 mm	3 x 0,14 mm ²	

Environmental Data		
Vibration	10 – 55 Hz, 0,5 mm	
Shock	30 g	
Light immunity, @ 0° incidence	-	20 000 lux
Temperature, operation	-20 to +50 °C	
Temperature, storage	-40 to +80 °C	
Sealing class	IP 67	
Approvals	CE UK EA	
Safety category	TÜV acc. EN 12978:2003 + A1:2009, EN ISO 13849-1:2015	

Available Types


Transmitter	Type	Control Feature	Output	Connection		5 m cable	15 m cable	0.15m cable with 3 pin, M8 plug	Range
				Housing Material	Housing Size	Order Reference			
3010C	Adjustable range and test input	-	-	Polycarbonate	Ø10	SMT 3010C/CAT2 AP 5	SMT 3010C/CAT2 AP 15	SMT 3010C/CAT2 AP 0.15/T3	1-10 m
				Nickel Plated Brass	M12 x 1	SMT 3010C/CAT2 TP 5	SMT 3010C/CAT2 TP 15	SMT 3010C/CAT2 TP 0.15/T3	
						SMT 3010C/CAT2 TB 5	SMT 3010C/CAT2 TB 15	SMT 3010C/CAT2 TB 0.15/T3	

Receiver	Type	Control Feature	Output	Connection		5 m cable	15 m cable	0.15m cable with 3 pin, M8 plug	Range
				Housing Material	Housing Size	Order Reference			
3010	-	-	NPN LO (NC)	Polycarbonate	Ø10	SMR 3010/CAT2 AP 5	SMR 3010/CAT2 AP 15	SMR 3010/CAT2 AP 0.15/T3	10 m
				Nickel Plated Brass	M12 x 1	SMR 3010/CAT2 TP 5	SMR 3010/CAT2 TP 15	SMR 3010/CAT2 TP 0.15/T3	
						SMR 3010/CAT2 TB 5	SMR 3010/CAT2 TB 15	SMR 3010/CAT2 TB 0.15/T3	
3210	-	-	PNP LO (NC)	Polycarbonate	Ø10	SMR 3210/CAT2 AP 5	SMR 3210/CAT2 AP 15	SMR 3210/CAT2 AP 0.15/T3	10 m
				Nickel Plated Brass	M12 x 1	SMR 3210/CAT2 TP 5	SMR 3210/CAT2 TP 15	SMR 3210/CAT2 TP 0.15/T3	
						SMR 3210/CAT2 TB 5	SMR 3210/CAT2 TB 15	SMR 3210/CAT2 TB 0.15/T3	


Connections

	Cable	M8 Plug / Cable
Supply +	Brown	Pin 1 / Brown
Supply -	Blue	Pin 3 / Blue
SMT control	Black	Pin 4 / Black
SMR output	Black	Pin 4 / Black


3 pin, M8




Wiring Diagrams



SMT 3010C/CAT2
Variable range and ON/OFF switch for transmitting power




SMR 3010/CAT2




SMR 3210/CAT2


Dimensions and Descriptions



AP 5/15/0.15/T3



TP/TB 5/15/0.15/T3




0.15/T3


(Units in mm)

Response Times


Range	SMT (test input reaction time)			SMR (output response time)	
	Ton (beam break)	Toff (beam make)	Tr (min)	Ton (beam break)	Toff (beam make)
2 m	14 ms	10 ms	20 ms	14 ms	10 ms
4 m	12 ms	11 ms	18 ms	12 ms	11 ms
6 m	11 ms	15 ms	17 ms	11 ms	15 ms
8 m	8 ms	29 ms	14 ms	8 ms	29 ms
10 m	8 ms	34 ms	14 ms	8 ms	34 ms



Angular Displacement




SMT 3010C/CAT2




SMR 3x10/CAT2




Applications



SECURITY AND DOORS
Vehicle and pedestrian detection



ACCESS CONTROL
Pedestrian detection



GATES
Vehicle and pedestrian detection

Telco reserves the right to change specifications without notice.